



DUCHESNE COUNTY MONUMENT SURVEY RECORD

T1N R1W
SEC 33
1/4
SEC 4
T1S R1W
U.S.B.&M.

Z-11



SCALE: 1"=30'



LINE	BEARING	DISTANCE
L1	N 29°12'31" E	65.51'
L2	N 42°00'28" E	47.30'
L3	N 46°49'05" E	46.42'
L4	N 59°03'11" E	61.49'
L5	N 58°05'29" W	59.98'
L6	S 08°21'03" W	32.20'

5/8"x24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT 1/16 CORNER

S 33

N 89°59'49" W
1331.06'

5/8"x24" REBAR WITH
A 2 1/2" ALUMINUM
DUCHESNE COUNTY
MONUMENT AT NORTH 1/4
CORNER SEC 4

S 4

N 89°58'25" W
2626.43'
(TIE ONLY, NOT
TWSP LINE)

C/L PIPE
FENCE CORNER

C/L PIPE
FENCE CORNER

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
(SECTION CORNER) LOCATED AT LAT. 40°23'20.57790"N
AND LONG. 110°01'46.98583"W USING THE UTAH STATE
G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A SURVEY MARKER AT THE
POSITION OF THE 1/4 CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES
ESTABLISHED TO PERPETUATE THE ORIGINAL
LOCATION OF THE CORNER

SET A 5/8"x24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY MONUMENT
AT THE POSITION OF THE 1/4 CORNER
AFTER ROAD CONSTRUCTION



STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
NAD83 UTAH CENTRAL ZONE
N: 7329928.953
E: 2057511.183
NAVD88 EL: 5970.04'

LATITUDE: 40°25'58.62033" N
LONGITUDE: 110°00'05.75279" W
ELLIPSOID HEIGHT: 5916.48'
(GEOID 03 CONUS)
PUBLIC LAND SURVEY SYSTEM GCDB ID NO.
UT300010S0010W0_340700

CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do
hereby certify that I have performed or reviewed the work done on the
diagrammed corner as reported on this recordation form and approve same

Date 28 FEB 2018

Jerry D. Allred, Professional Land Surveyor
Certificate No. 148951
Duchesne County Surveyor

